

Carburetor & Choke Cleaner Spray

Cleaner for carburetors, chokes and throttle bodies

AER2605

PRODUCT DESCRIPTION

DVX Carburetor & Choke Cleaner Spray quickly removes gum, varnish, carbon and oxidised fuel deposits inside and outside carburetors, chokes and throttle bodies. It restores air and fuel flow, helping to regain a stable idle, better throttle response and controlled fuel consumption.
Suitable for cars, motorcycles, scooters, lawn mowers and small engines. The extension tube reaches jets and narrow passages.

FEATURES

- Removes gum and carbon
- Restores airflow
- Smoother idle
- Carburetor, choke, throttle
- Car, moto, small engines
- Extension tube

DIRECTIONS FOR USE

1. **Prepare** — Engine off and cold; remove the air filter.
2. **Spray** — Spray onto the throttle plate and into the carburetor passages.
3. **Let work** — Leave 2–3 minutes; repeat on stubborn deposits.
4. **Reassemble** — Refit the filter, start the engine and let it idle a few minutes.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol carburettor cleaner
Appearance	Aerosol
Odour	Characteristic
pH	5-7
Density (20 °C)	0.75-0.80 g/mL
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER2605	500 ml	24 per case	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H350 May cause cancer.
H340 May cause genetic defects.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking. Restricted to professional users.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr