

Contact Cleaning Spray

Oil-free cleaning spray for electrical and electronic contacts

AER1409 **AER1400**

PRODUCT DESCRIPTION

Used to clean electrical and electronic parts from dust, oil and other dirt. Does not leave a mark as it evaporates quickly. Provides resistance against external effects such as moisture, rust and corrosion. Can be used on home appliances, garden equipment, car door and trunk locks, headlight holders, plugs and zippers, hinges, locks and curtain rails, as well as for oil cleaning. Helps solve problems in electrical and electronic circuits. Re-lubrication may be needed after surface cleaning. Periodic applications may extend component life.

FEATURES

- Deep contact cleaning
- Zero-oil residue
- 360° spray
- Full-cover cap
- Fast-evaporating formula
- Helps fight corrosion

DIRECTIONS FOR USE

1. **Shake & power off** — Shake well. Disconnect all power completely.
2. **Spray from 15-20 cm** — Apply evenly to electrical and electronic contacts.
3. **Let dirt dissolve** — Wait briefly. Wipe clean or use compressed air if needed.
4. **Dry completely** — Restart only when fully dry. Can be used upside down.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1409	200 ml	24	8682960810831
AER1400	400 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).