

Cooling System Stop Leak

Super sealant for cooling systems, cylinder blocks and head gaskets

AER3106

PRODUCT DESCRIPTION

Cylinder and cooling system leak sealer (super sealant). Seals small leaks and hairline cracks in radiators, engine cylinder blocks, water pumps, heater cores and head gaskets. Also suitable for industrial boilers and hot-water pipes.

FEATURES

- Seals leaks in radiators and cooling systems
- For cylinder blocks, water pumps, heater cores and head gaskets
- Also for industrial boilers and hot-water pipes
- Water-based formula
- 350 g bottle

DIRECTIONS FOR USE

1. Drain and flush the cooling system with clean water. Do not pour into a radiator containing antifreeze.
2. With the engine cold, pour the product into the radiator and top up with water.
3. Start the engine and let it run for 10–15 minutes.
4. Leave the product in the system for at least 2 hours.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Colour	Blue
Odour	Characteristic
pH	12 – 13
Flash point	Not applicable (aqueous product)
Solubility in water	Miscible

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER3106	350 g	12	8682960815904

STORAGE

Store in the original, tightly closed container in a cool, dry place. Protect from frost and direct sunlight. Keep out of reach of children.

SAFETY INFORMATION



Signal word: Warning

- H373 – May cause damage to organs through prolonged or repeated exposure.
- H319 – Causes serious eye irritation.
- H315 – Causes skin irritation.
- P102 – Keep out of reach of children.
- P264 – Wash hands thoroughly after handling.
- P280 – Wear protective gloves / eye protection / face protection.
- P337+P313 – If eye irritation persists: Get medical advice / attention.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).