

Diesel Additive

Fuel additive for diesel engines, prevents gelling and freezing

AER3204

PRODUCT DESCRIPTION

It prevents gelling and freezing in fuel. Ensures easier engine running in cold. Provides better combustion in fuel. Increases engine power and saves money. Clears residues, reduces power loss on the motor. Reduces maintenance costs and exhaust fumes and contamination.

FEATURES

- Deep fuel clean
- Cetane power boost
- Smoother engine run
- Lower fuel consumption
- DPF, turbo & common-rail safe
- One can treats up to 75 L

DIRECTIONS FOR USE

1. **Check the dosage** — One 300 ml can treats up to 75 L of diesel fuel.
2. **Add before refueling** — Pour the entire can into the diesel fuel tank before refueling.
3. **Refuel & mix** — Fill the tank with diesel to mix the additive evenly.
4. **Use regularly** — Use periodically or after fuel-system service. Suitable for diesel and biodiesel blends.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Liquid
Colour	Colorless
Odour	Characteristic
Density (20 °C)	0.80-0.81 g/cm³
Solubility in water	Not soluble in water
Flammability	Flammable
Flash point	11,7 - 12 °C
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER3204	300 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P370+P378 In case of fire: use . . . to extinguish.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).