

Egr Cleaner Spray

Cleaning spray for the EGR valve and air-intake system

AER2601

PRODUCT DESCRIPTION

Special mixture of solvents to provide internal and outer cleaning for fuel injection system parts. Injection system parts, idling valves, choke and air intakes can be cleaned instantly and safely without smearing. Fuel Injection Air-Intake System Cleaner is completely safe for oxygen sensors and catalytic converters. Thanks to its additional special lubricating feature which allows carburetor parts to work properly. Available to be used as an oil and gasoline stain cleaner in industry, assembly and maintenance services.

FEATURES

- Rapid carbon breakdown
- Sensor & catalyst safe
- No disassembly needed
- Restores airflow & performance
- 500 ml aerosol
- Protective cap

DIRECTIONS FOR USE

1. **Shake & attach** — Shake well and attach the extension tube.
2. **Spray from 20 cm** — Spray directly onto the dirty surface.
3. **Wait & clean** — Wait a few minutes, then wipe or brush. Repeat if needed.
4. **Finish the system** — For intake cleaning, start the engine after completion.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER2601	500 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H350 May cause cancer.
H340 May cause genetic defects.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr