

Engine Oil Leak Preventer

(270 ml) Engine oil additive that stops leaks without disassembly

AER3505

PRODUCT DESCRIPTION

DVX Engine Oil Leak Preventer is an additive for engine oil. It rejuvenates and softens rubber seals and gaskets hardened by age and heat, preventing and stopping oil leaks and seepage without engine disassembly. It helps restore performance and limits oil consumption. Compatible with all mineral and synthetic oils, petrol and diesel engines.

FEATURES

- Stops oil leaks
- No disassembly
- Rejuvenates seals
- Limits oil consumption
- Restores performance
- Petrol and diesel

DIRECTIONS FOR USE

1. Prepare — Warm engine, then switch off and check the oil level.
2. Add — Pour the bottle into the engine oil.
3. Drive — Drive normally; the effect appears after a few hundred km.
4. Check — Check the oil level regularly.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid (paste-like)
Colour	Yellow
Odour	Characteristic
Flash point	> 100 °C
Relative density	0.896
Kinematic viscosity	≈ 1300 mm²/s
pH	Not applicable (non-aqueous)
Solubility in water	Insoluble

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER3505	270 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place. The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION



Signal word: Danger

- H318 – Causes serious eye damage.
- H336 – May cause drowsiness or dizziness.
- P102 – Keep out of reach of children.
- P261 – Avoid breathing vapours / spray.
- P271 – Use only outdoors or in a well-ventilated area.
- P280 – Wear protective gloves / eye protection / face protection.
- P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 – Immediately call a POISON CENTRE / doctor.
- P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P405 – Store locked up.
- P501 – Dispose of contents / container to an approved waste disposal facility.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).