

Safety Data Sheet (SDS)

Fuel Injector Cleaner

AER3305

Product name on SDS	DVX FUEL INJECTOR CLEANER
Revision / date	Rev. 3 · 12.11.2026
Regulation	REACH Annex II — Regulation (EU) 2020/878 · CLP (EC) 1272/2008
Supplier	Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Emergency	+90 216 669 03 53 · UZEM 114
UFI	NR49-40AT-N007-UPV0



Danger

- H304 – May be fatal if swallowed and enters airways.
- H412 – Harmful to aquatic life with long lasting effects.
- EUH066 – Repeated exposure may cause skin dryness or cracking.

This cover page identifies the product. The following pages form the Safety Data Sheet of the product.

SAFETY DATA SHEET

According to Annex II to REACH – Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2020/878
DVX FUEL INJECTOR CLEANER · AER3305 · Rev. 3 · 12.11.2026

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name	DVX FUEL INJECTOR CLEANER
Product code	AER3305
UFI	NR49-40AT-N007-UPV0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use	Fuel additive – gasoline injection system cleaner (machine and tank application)
Uses advised against	No information available at present.

1.3 Details of the supplier of the safety data sheet

Company	SETKIM KIMYA İNŞ. TAAH. PAZ. SAN. TİC. LTD. ŞTİ.
Address	İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel, Fikse Cad. No:20, 34935 Tuzla / İstanbul, Türkiye
Telephone	+90 216 669 03 53 · +90 850 259 0389
Fax	+90 216 669 03 50
E-mail (competent person responsible for the SDS)	info@divortex.com.tr
Brand	DVX / Divortex

1.4 Emergency telephone number

Company emergency number	+90 216 669 03 53 (office hours)
National Poison Information Centre (Türkiye, UZEM)	114 (24 h)
Other countries	Contact the national poison centre of the country of use.

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Hazard class	Category	Hazard statement
Asp. Tox.	1	H304 – May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412 – Harmful to aquatic life with long lasting effects.

2.2 Label elements



Danger

Hazard statements:

- H304 – May be fatal if swallowed and enters airways.
- H412 – Harmful to aquatic life with long lasting effects.

Precautionary statements:

- P101 – If medical advice is needed, have product container or label at hand.
- P102 – Keep out of reach of children.
- P273 – Avoid release to the environment.
- P301+P310 – IF SWALLOWED: Immediately call a POISON CENTRE / doctor.
- P331 – Do NOT induce vomiting.
- P405 – Store locked up.
- P501 – Dispose of contents / container to an approved waste disposal facility.

Supplemental hazard information:

- EUH066 – Repeated exposure may cause skin dryness or cracking.

Hazardous components which must be listed on the label: Hydrocarbons, C10, aromatics, <1% naphthalene; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics.

2.3 Other hazards

- The mixture does not contain any PBT or vPvB substance (< 0.1 %).
- The mixture does not contain substances with endocrine disrupting properties (< 0.1 %).
- Vapours are heavier than air.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Component	EC / List no.	CAS	REACH reg. no.	Content %	Classification (CLP)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	918-481-9	—	01-2119457273-39	75 – <100	Asp. Tox. 1, H304; EUH066
Hydrocarbons, C10, aromatics, <1% naphthalene	918-811-1	(64742-94-5)	01-2119463583-34	2.5 – <10	STOT SE 3, H336; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; EUH066

Full text of H and EUH statements: see Section 16. Note P applied (benzene < 0.1 %). As the naphthalene content of the product is < 1 %, classification as Carc. 2, H351 is not required.

4. FIRST AID MEASURES

4.1 Description of first aid measures

General	First-aiders should protect themselves. Never give anything by mouth to an unconscious person.
Inhalation	Remove person from the danger area. Supply fresh air and consult a doctor according to symptoms.
Skin contact	Remove contaminated clothing immediately, wash thoroughly with plenty of water and soap; in case of skin irritation (redness) consult a doctor.
Eye contact	Remove contact lenses. Rinse thoroughly with plenty of water for several minutes. Seek medical help if necessary.
Ingestion	Rinse mouth thoroughly with water. Do NOT induce vomiting. Consult a doctor immediately. If vomiting occurs, keep head low so that stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

Skin redness, drying of the skin, nausea, vomiting, danger of aspiration, pulmonary oedema, chemical pneumonitis. Symptoms may appear only after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment. Gastric lavage only under endotracheal intubation. Subsequent observation for pneumonia and pulmonary oedema.

5. FIREFIGHTING MEASURES

5.1 Suitable extinguishing media	CO2, dry powder, foam, water spray.
Unsuitable extinguishing media	Full water jet.
5.2 Special hazards	In case of fire: carbon oxides, sulphur oxides and toxic gases may be formed.
5.3 Advice for firefighters	Do not breathe explosion and combustion gases. Use self-contained breathing apparatus and, depending on the size of the fire, full protection. Cool endangered containers with water. Dispose of contaminated extinguishing water according to official regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions	Wear personal protective equipment (see Section 8). Ensure sufficient ventilation, remove ignition sources. Avoid contact with eyes and skin. Risk of slipping.
6.2 Environmental precautions	Dam up larger spills. Stop leaks if possible without risk. Prevent entry into surface water, groundwater, soil, sewers and pits. Inform authorities in case of entry into drains.
6.3 Methods for containment and cleaning up	Soak up with liquid-binding material (e.g. universal binder) and dispose of according to Section 13.
6.4 Reference to other sections	See Section 8 for PPE and Section 13 for disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling	Ensure good ventilation. Avoid breathing vapours. Keep away from ignition sources – no smoking. Do not heat to temperatures close to the flash point. Avoid contact with eyes and skin. Do not eat, drink or smoke in work areas. Wash hands before breaks and after work.
7.2 Conditions for safe storage	Keep out of reach of unauthorised persons. Store only in the original, closed packaging. Do not store in gangways or stairwells. Solvent-resistant floor. Do not store with oxidising agents. Protect from sunlight and heat. Store in a well-ventilated place.
7.3 Specific end use(s)	Fuel system cleaner. Follow the instructions on the label and of the cleaning-machine manufacturer.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Component	Limit value	Note
Mixture (total hydrocarbon solvent content)	TWA 550 mg/m³	Group guidance value (RCP method)
Hydrocarbons, C10-C13, <2% aromatics	TLV-TWA 1000 mg/m³ (ACGIH)	RCP method

Hydrocarbons, C10, aromatics, <1% naphthalene	TLV-TWA 100 mg/m³	C9-C15 aromatics

8.2 Exposure controls

Engineering controls	Ensure good ventilation (local exhaust or general extraction). Use respiratory protection if limit values are exceeded.
Eye / face protection	Tight-fitting safety goggles with side protection (EN ISO 16321-1).
Hand protection	Chemical-resistant gloves (EN ISO 374), e.g. nitrile, neoprene/polychloroprene or Viton®/fluoroelastomer, min. thickness 0.5 mm, breakthrough time 480 min. Protective hand cream recommended.
Skin / body protection	Protective work clothing (long sleeves), safety shoes (EN ISO 20345).
Respiratory protection	If the workplace limit value is exceeded: filter A (EN 14387), colour code brown.
Environmental exposure controls	Prevent release into drains and the environment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Colour	Yellow
Odour	Aromatic
Melting / freezing point	No data available
Boiling point / range	No data available
Flammability	No data available
Explosion limits	No data available
Flash point	>61 °C
Auto-ignition temperature	No data available
pH	Not applicable
Kinematic viscosity	1.57 mm²/s (40 °C)
Solubility in water	Insoluble
Partition coefficient n-octanol/water	Not applicable to mixtures
Vapour pressure	No data available
Density	0.808 g/ml (20 °C)
VOC (Directive 2010/75/EU)	97.7 %

10. STABILITY AND REACTIVITY

10.1 Reactivity	The product has not been tested.
10.2 Chemical stability	Stable under proper storage and handling.
10.3 Possibility of hazardous reactions	No dangerous reactions known.
10.4 Conditions to avoid	Heating, open flames, ignition sources.
10.5 Incompatible materials	Strong oxidising agents.
10.6 Hazardous decomposition products	None when used as directed.

11. TOXICOLOGICAL INFORMATION

No test data are available for the mixture; classification according to calculation method: Asp. Tox. 1, H304. Data for components:

Component	Endpoint	Value
C10-C13 hydrocarbons	LD50 oral (rat, OECD 401)	>5000 mg/kg
C10-C13 hydrocarbons	LD50 dermal (rabbit, OECD 402)	>3160 mg/kg
C10-C13 hydrocarbons	LC50 inhalation (rat, 4 h)	>4951 mg/m³
C10-C13 hydrocarbons	Irritation / sensitisation / mutagenicity / carcinogenicity / reproduction	Negative / not irritant
C10 aromatics, <1% naphthalene	LD50 oral (rat) / dermal (rabbit)	>5000 / >2000 mg/kg
C10 aromatics, <1% naphthalene	LC50 inhalation (rat, 4 h)	>4688 mg/m³
C10 aromatics, <1% naphthalene	STOT SE	May cause drowsiness or dizziness (H336)

Aspiration hazard: yes. Possible symptoms: unconsciousness, headache, dizziness, skin dryness, nausea, vomiting.

11.2 Information on other hazards

The mixture does not contain endocrine disrupting substances (< 0.1 %).

12. ECOLOGICAL INFORMATION

No test data available for the mixture. Classified Aquatic Chronic 3, H412 (calculation method). AOX: 0 % (according to formulation). Data for components:

Component	Endpoint	Value
C10-C13 hydrocarbons	LL50 fish 96 h / EL50 daphnia 48 h / EL50 algae 72 h	>1000 mg/l
C10-C13 hydrocarbons	NOELR fish 28 d / daphnia 21 d	0.101 / 0.176 mg/l
C10-C13 hydrocarbons	Biodegradation (OECD 301F, 28 d)	80 – 89.8 % – readily biodegradable
C10 aromatics	LC50 fish 96 h / EC50 daphnia 48 h / EC50 algae 72 h	2–5 / 3–10 / 1–3 mg/l
C10 aromatics	Biodegradation (OECD 301F, 28 d)	49.6 % – inherently biodegradable
C10 aromatics	BCF	<100 (low)

12.5 PBT/vPvB	Not PBT / vPvB.
12.6 Endocrine disrupting properties	Not applicable to mixtures.
12.7 Other adverse effects	Harmful to aquatic life with long lasting effects. Product floats on water.

13. DISPOSAL CONSIDERATIONS

Waste code (recommendation)	07 07 04* – other organic solvents, washing liquids and mother liquors
Product	Do not discharge into sewers. Rags and absorbents soaked with product present a fire hazard and must be collected and disposed of in a controlled manner. Dispose of via a licensed waste disposal company, e.g. suitable incineration plant.
Contaminated packaging	Empty completely. Uncontaminated packaging can be recycled; packaging that cannot be cleaned is disposed of like the product.

14. TRANSPORT INFORMATION

Not classified as dangerous goods for transport (ADR/RID, IMDG, IATA). 14.1 – 14.5: Not applicable. 14.7: Not dangerous according to MARPOL 73/78 Annex II / IBC Code.

15. REGULATORY INFORMATION

15.1 Specific provisions	Regulation (EC) No 1907/2006 (REACH), Regulation (EC) No 1272/2008 (CLP); national occupational health and safety rules. VOC (2010/75/EU): 97.7 %.
15.2 Chemical safety assessment	Not carried out for the mixture.

16. OTHER INFORMATION

Revision	Rev. 3 · 12.11.2026 – replaces Rev. 2 · 16.09.2025. New formulation (non-aerosol liquid); composition, classification and Sections 1–16 updated.
Classification procedure	Asp. Tox. 1 H304 and Aquatic Chronic 3 H412: calculation method.

Relevant H and EUH statements (Sections 2 and 3):

- H304 – May be fatal if swallowed and enters airways.
- H336 – May cause drowsiness or dizziness.
- H411 – Toxic to aquatic life with long lasting effects.
- H412 – Harmful to aquatic life with long lasting effects.
- EUH066 – Repeated exposure may cause skin dryness or cracking.

Training of employees in the handling of hazardous substances is required. The information in this SDS is based on our current knowledge and applies to the product as supplied; it does not constitute a guarantee of product properties.