

General Cleaning Spray

Universal cleaning spray that removes oil and grease from surfaces

AER1000

PRODUCT DESCRIPTION

DVX General Cleaning Spray is a fast-evaporating technical cleaner for workshops, garages and industry. It quickly dissolves oil, grease, brake dust and machining residue on metal parts, brakes, clutches, engines and tools. It evaporates without leaving an oily film, making subsequent assembly, bonding or painting easier. Thanks to its 360° valve, it can be used in any position, even in hard-to-reach areas.

FEATURES

- Dissolves oil and grease
- Fast evaporation, no residue
- Brakes, engines and mechanical parts
- Prepares for bonding and painting
- 360° valve, any position
- Workshop and industrial use

DIRECTIONS FOR USE

1. **Prepare** — Remove coarse dirt. Work on a cold engine.
2. **Shake** — Shake the can well before use.
3. **Spray** — Spray from 20–30 cm onto the area and let it work for a few seconds.
4. **Let dry** — Let it evaporate or wipe with a clean cloth. Repeat if necessary.

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol brake & clutch cleaner
Appearance	Aerosol
Odour	Characteristic
Density (20 °C)	0.70-0.75 g/cm³
Solubility in water	Insoluble in water
Flammability	Flammable
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1000	500 ml	24 per case	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H351 Suspected of causing cancer.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr