

Safety Data Sheet (SDS)

Motorcycle Helmet Glass Cleaning Spray

AER1801

Product name on SDS	DVX MOTORCYCLE HELMET GLASS CLEANING SPRAY
Revision / date	Rev. 2 · 12.11.2026
Regulation	REACH Annex II — Regulation (EU) 2020/878 · CLP (EC) 1272/2008
Supplier	Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Emergency	+90 216 669 03 53 · UZEM 114



Danger

- H222 – Extremely flammable aerosol.
- H229 – Pressurised container: May burst if heated.
- H319 – Causes serious eye irritation.

This cover page identifies the product. The following pages form the Safety Data Sheet of the product.

SAFETY DATA SHEET

According to Annex II to REACH – Regulation (EC) No 1907/2006, as amended by Regulation (EU) 2020/878
DVX MOTORCYCLE HELMET GLASS CLEANING SPRAY · AER1801 · Rev. 2 · 12.11.2026

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product name	DVX MOTORCYCLE HELMET GLASS CLEANING SPRAY
Product code	AER1801
UFI	32X2-H9RF-N008-S32K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use	Cleaning product – helmet visor / glass cleaner (aerosol).
Uses advised against	No information available at present.

1.3 Details of the supplier of the safety data sheet

Company	SETKIM KIMYA İNŞ. TAAH. PAZ. SAN. TİC. LTD. ŞTİ.
Address	İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel, Fikse Cad. No:20, 34935 Tuzla / İstanbul, Türkiye
Telephone	+90 216 669 03 53 · +90 850 259 0389
Fax	+90 216 669 03 50
E-mail (competent person responsible for the SDS)	info@divortex.com.tr
Brand	DVX / Divortex

1.4 Emergency telephone number

Company emergency number	+90 216 669 03 53 (office hours)
National Poison Information Centre (Türkiye, UZEM)	114 (24 h)
Other countries	Contact the national poison centre of the country of use.

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Hazard class	Category	Hazard statement
Aerosol	1	H222 – Extremely flammable aerosol.
Aerosol	1	H229 – Pressurised container: May burst if heated.
Eye Irrit.	2	H319 – Causes serious eye irritation.

2.2 Label elements



Danger

Hazard statements:

- H222 – Extremely flammable aerosol.
- H229 – Pressurised container: May burst if heated.
- H319 – Causes serious eye irritation.

Precautionary statements:

- P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 – Do not spray on an open flame or other ignition source.
- P251 – Do not pierce or burn, even after use.
- P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- P280 – Wear eye protection / face protection.
- P337+P313 – If eye irritation persists: Get medical advice / attention.

Supplemental hazard information:

2.3 Other hazards

- The mixture does not contain any PBT or vPvB substance (< 0.1 %).
- The mixture does not contain substances with endocrine disrupting properties (< 0.1 %).

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Component	EC / List no.	CAS	REACH reg. no.	Content %	Classification (CLP)
Water	231-791-2	7732-18-5	—	60 – <70	Not classified
Petroleum gases, liquefied (1,3-butadiene < 0.1 %)	270-704-2	68476-85-7	—	30 – <38	Flam. Gas 1A, H220; Press. Gas, H280 (Note K, S, U)
Propan-2-ol (isopropyl alcohol)	200-661-7	67-63-0	01-2119457558-25	7 – <10	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336
Alcohols, C12-14, ethoxylated, sulfates, sodium salts	500-234-8	68891-38-3	—	1 – <2	Eye Dam. 1, H318; Skin Irrit. 2, H315; Aquatic Chronic 3, H412

Full text of H statements: see Section 16. The product is an aerosol containing propellants; percentages include the propellant. For the health-hazard calculation the propellant is not considered.

4. FIRST AID MEASURES

General	First-aiders should ensure they are protected. Never pour anything into the mouth of an unconscious person.
Inhalation	Remove person from danger area. Supply fresh air and consult a doctor according to symptoms.
Skin contact	Remove contaminated, soaked clothing immediately, wash thoroughly with plenty of water and soap; in case of skin irritation (redness) consult a doctor.
Eye contact	Remove contact lenses. Rinse thoroughly for several minutes with plenty of water. Seek medical help if necessary.
Ingestion	Typically no exposure route. Rinse mouth thoroughly with water. Give plenty of water to drink – consult a doctor immediately.
4.2 Symptoms	Delayed symptoms may appear after several hours. Sensitive individuals: allergic reaction possible.

4.3 Treatment	Symptomatic treatment.

5. FIREFIGHTING MEASURES

5.1 Suitable extinguishing media	Water spray, foam, CO2, dry powder.
Unsuitable extinguishing media	High volume water jet.
5.2 Special hazards	Carbon oxides, nitrogen oxides, toxic gases. Danger of bursting (explosion) when heated. Explosive vapour/air mixtures.
5.3 Advice for firefighters	Do not breathe fumes. Self-contained breathing apparatus; full protection according to the size of the fire. Cool containers at risk with water. Dispose of contaminated extinguishing water according to official regulations.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions	Wear personal protective equipment (Section 8). Ensure sufficient ventilation, remove ignition sources. Avoid contact with eyes and skin.
6.2 Environmental precautions	Prevent entry into surface water, groundwater, soil and drains.
6.3 Methods for cleaning up	Soak up with liquid-binding material (e.g. universal binder) and dispose of according to Section 13.
6.4 Reference to other sections	PPE: Section 8; disposal: Section 13.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling	Ensure good ventilation. Keep away from ignition sources – no smoking. Avoid contact with eyes and skin. Do not eat, drink or smoke in work areas. Wash hands before breaks and after work.
7.2 Conditions for safe storage	Keep out of reach of unauthorised persons. Store closed and only in original packaging. Do not store with oxidising agents. Observe regulations for aerosols. Protect from direct sunlight and temperatures above 50 °C. Store in a well-ventilated place.
7.3 Specific end use(s)	Helmet visor / glass cleaner. Follow the label instructions.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Component	TWA	STEL
Propan-2-ol	400 ppm (999 mg/m³)	500 ppm (1250 mg/m³)
Butane	600 ppm (1450 mg/m³)	750 ppm (1810 mg/m³)
Propane / isobutane	1000 ppm (ACGIH)	—

Propan-2-ol DNEL (workers): inhalation, long term 500 mg/m³; dermal, long term 888 mg/kg bw/day.

8.2 Exposure controls

Engineering controls	Ensure good ventilation (local exhaust or general extraction).
Eye / face protection	Tight-fitting goggles with side protection (EN ISO 16321-1).
Hand protection	Nitrile gloves (EN ISO 374), min. 0.35 mm.
Skin / body protection	Protective working garments (long sleeves).

Respiratory protection	Normally not necessary. If the workplace limit is exceeded: filter A (EN 14387), brown.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol. Active substance: liquid.
Colour	Colourless
Odour	Characteristic
Melting / boiling point	No data available
Flammability	Not applicable to aerosols (Aerosol 1)
Explosive properties	Risk of explosion at temperatures above 50 °C.
pH	7.5
Solubility	Miscible with water (active substance)
Partition coefficient n-octanol/water	Not applicable to mixtures
Density	0.80 – 0.81 g/ml
Particle characteristics	Not applicable

10. STABILITY AND REACTIVITY

10.1 Reactivity	The product has not been tested.
10.2 Chemical stability	Stable with proper storage and handling.
10.3 Hazardous reactions	None known.
10.4 Conditions to avoid	Heating, open flame, ignition sources. Pressure increase will result in danger of bursting.
10.5 Incompatible materials	Oxidising agents.
10.6 Hazardous decomposition products	None when used as directed.

11. TOXICOLOGICAL INFORMATION

Mixture: Eye Irrit. 2, H319 (calculation method). Other health hazard classes: classification criteria not met. Data for components:

Component	Endpoint	Value
Propan-2-ol	LD50 oral (rat) / dermal (rabbit)	5045 / 12800 mg/kg
Propan-2-ol	LC50 inhalation (rat, 4 h)	> 25 mg/l
Propan-2-ol	Eye irritation / STOT SE	Eye Irrit. 2 / STOT SE 3 (H336)
C12-14 alcohol ethoxy sulfate, Na	Eye / skin	Eye Dam. 1 / Skin Irrit. 2

Possible symptoms: eye redness and watering; at high vapour concentrations drowsiness or dizziness.

12. ECOLOGICAL INFORMATION

No test data for the mixture; not classified as hazardous to the aquatic environment. Propan-2-ol and the propellant gases are readily biodegradable; the surfactant complies with the biodegradability criteria of Regulation (EC) No 648/2004.

12.5 PBT/vPvB	Not PBT / vPvB.
12.6 Endocrine disrupting properties	Not applicable to mixtures.

13. DISPOSAL CONSIDERATIONS

Waste code (recommendation)	16 05 04* gases in pressure containers containing hazardous substances; 20 01 29* detergents containing hazardous substances
Product	Do not discharge into sewers. Take full aerosol cans to hazardous waste collection; empty cans to recycling. Observe local regulations.
Contaminated packaging	15 01 04 metallic packaging; 15 01 10* packaging containing residues of hazardous substances. Do not perforate, cut up or weld uncleaned containers.

14. TRANSPORT INFORMATION

	ADR/RID	IMDG	IATA
14.1 UN number	1950	1950	1950
14.2 Proper shipping name	UN 1950 AEROSOLS	UN 1950 AEROSOLS	UN 1950 Aerosols, flammable
14.3 Class	2.1 (5F)	2.1	2.1
14.4 Packing group	—	—	—
14.5 Environmental hazards	No	No (not a marine pollutant)	No
Other	LQ 1 L; tunnel code D; transport category 2	EmS F-D, S-U	—

15. REGULATORY INFORMATION

15.1 Specific provisions	Regulation (EC) 1907/2006 (REACH), (EC) 1272/2008 (CLP), Directive 75/324/EEC (aerosols), Regulation (EC) 648/2004 (detergents). Seveso III (2012/18/EU): P3a. REACH Annex XVII: entries 40 and 75. Observe national rules on protection of young people and maternity at work.
15.2 Chemical safety assessment	Not carried out for the mixture.

16. OTHER INFORMATION

Revision	Rev. 2 · 12.11.2026 – replaces Rev. 1 · 08.08.2025. Converted to DVX format; Section 9 updated (pH measured: 7.5).
Classification procedure	Aerosol 1, H222/H229: form / physical state; Eye Irrit. 2, H319: calculation method.

Relevant H statements (Sections 2 and 3):

- H222 – Extremely flammable aerosol.
- H229 – Pressurised container: May burst if heated.
- H220 – Extremely flammable gas.
- H280 – Contains gas under pressure; may explode if heated.
- H225 – Highly flammable liquid and vapour.
- H315 – Causes skin irritation.
- H318 – Causes serious eye damage.
- H319 – Causes serious eye irritation.
- H336 – May cause drowsiness or dizziness.
- H412 – Harmful to aquatic life with long lasting effects.

Training of employees in the handling of hazardous substances is required. The information in this SDS is based on our current knowledge and applies to the product as supplied; it does not constitute a guarantee of product properties.