

Injector Cleaner Spray

Cleaning spray for the fuel injection, carburetor and air-intake system

AER2201

PRODUCT DESCRIPTION

Special mixture of solvents to provide internal and external cleaning. Injection system parts, idling valves, choke and air intakes can be cleaned instantly and safely without smearing. Completely safe for oxygen sensors and catalytic converters. Thanks to its additional special lubricating feature which allows carburetor parts to work properly. 360-degree use.

FEATURES

- Deep injector clean
- Restores fuel flow
- Carbon & resin removal
- Sensor & catalyst safe
- Gasoline & diesel
- Injection, carb & intake

DIRECTIONS FOR USE

1. **Shake well** — Shake the can thoroughly before use.
2. **Spray from 15-20 cm** — Spray evenly onto the part from 15-20 cm.
3. **Wait & loosen dirt** — Allow carbon and grime to dissolve briefly.
4. **Brush or reapply** — Repeat if needed or use a suitable brush.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Odour	Characteristic
Density (20 °C)	0,75-0,80 g/ml
Solubility in water	Insoluble in water
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER2201	500 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H350 May cause cancer.
H340 May cause genetic defects.
H304 May be fatal if swallowed and enters airways.
H373 May cause damage to organs through prolonged or repeated exposure.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects. Restricted to professional users.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr