

Liquid Grease Spray

General-purpose lubricant with fast penetration and high hold

AER1200

PRODUCT DESCRIPTION

General purpose lubricant spray with fast penetration and high holding on surfaces. Widely used in industrial areas as a general lubricant, as well as at homes where lubrication is needed.

FEATURES

- Fast penetration
- Friction & wear control
- Clear-finish formula
- Corrosion-resistant shield
- Water-repellent protection
- Silicone, resin & acid free

DIRECTIONS FOR USE

1. Clean & dry — Clean the surface and allow it to dry.
2. Shake well — Shake the can thoroughly before use.
3. Spray from 15-20 cm — Apply an even coat to the surface.
4. Wait 1-2 minutes — Allow it to penetrate. Repeat if needed.

PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol. Active substance: liquid.
Colour	Colourless / transparent
Odour	Characteristic
Density	0.70 – 0.80 g/ml (20 °C)
pH	Not applicable (non-aqueous)
Solubility in water	Insoluble

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1200	400 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place. The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION




Signal word: Danger

- H222 – Extremely flammable aerosol.
- H229 – Pressurised container: May burst if heated.
- H304 – May be fatal if swallowed and enters airways.
- P102 – Keep out of reach of children.
- P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 – Do not spray on an open flame or other ignition source.
- P251 – Do not pierce or burn, even after use.
- P410+P412 – Protect from sunlight. Do not expose to temperatures exceeding 50 °C.
- P301+P310 – IF SWALLOWED: Immediately call a POISON CENTRE / doctor.
- P331 – Do NOT induce vomiting.
- P501 – Dispose of contents / container to an approved waste disposal facility.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).