

Multi Purpose Care Spray

All-in-one spray that cleans, lubricates, loosens and protects

AER1305 **AER1300**

PRODUCT DESCRIPTION

Lubricates, cleans, loosens, protects and preserves. It keeps moving parts moving. It loosens stubbornly rusted and burnt-on screws quickly. Infiltrates and removes dirt and stubborn oil and grease residues. Provides protection against rust and corrosion. Drives away water.

FEATURES

- 3-in-1 clean, lube & protect
- Frees stuck parts
- Deep-reach penetration
- Long-lasting adhesion
- Moisture & corrosion shield
- Quieter, smoother motion

DIRECTIONS FOR USE

1. **Test first** — Check a small hidden area on delicate or painted surfaces.
2. **Shake & prepare** — Shake well. Make sure the surface is clean and suitable.
3. **Spray & wait** — Apply and allow it to penetrate. Repeat if needed.
4. **Use at any angle** — The 360° valve works sideways or upside down.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Aerosol / automotive additive
Appearance	Aerosol
Odour	Characteristics
Density (20 °C)	0,68-0,70 g/ml
Solubility in water	Insoluble in water
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1305	200 ml	24	—
AER1300	400 ml	24	—

STORAGE

Pressurised container: protect from sunlight and do not expose to temperatures above 50 °C. Do not pierce or burn, even after use. Store in a cool, well-ventilated place.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.
H350 May cause cancer.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects. Restricted to professional users.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do no expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr