

Orange Engineering Gasket Maker

Orange anaerobic liquid gasket for rigid metal flanges

AER1606

PRODUCT DESCRIPTION

DVX Orange Engineering Gasket Maker is an anaerobic liquid gasket that cures between two rigid metal surfaces once air is excluded. It replaces or supplements pre-cut gaskets on gearbox housings, oil pans, covers, pump flanges and differential casings. It fills surface irregularities, resists oils, fuels and coolants and prevents leaks. The product stays liquid outside the joint, making excess easy to clean up.

FEATURES

- Replaces pre-cut gaskets
- Fills surface irregularities
- Resists oils and fuels
- Housings, flanges, covers
- Excess easy to clean
- Anaerobic curing

DIRECTIONS FOR USE

1. **Clean** — Remove the old gasket, degrease and dry both faces.
2. **Apply** — Apply a continuous bead on one face, circling the bolt holes.
3. **Assemble** — Assemble the parts and tighten to the specified torque.
4. **Let cure** — Allow to cure before service and refilling with fluid.

PHYSICAL AND CHEMICAL PROPERTIES

Product type	Anaerobic threadlocker
Appearance	Liquid
Odour	Acrylate, characteristic
Density (20 °C)	1.035 g/ml
Use	Ready to use (apply undiluted)

PACKAGING

Product Code	Pack Size	Units per Case	Barcode (EAN-13)
AER1606	50 ml	24 per case	8682960810794

STORAGE

Store in the original container, tightly closed, between 5 and 35 °C, in a cool, dry place away from direct sunlight. Protect from frost.

The expiry date, production date and lot number are printed on the pack.

SAFETY INFORMATION

Signal word: Danger
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr