


# DVX PPF Deep Prep Liquid (1 L)

**Surface prep before PPF installation, antistatic formula**

**DVX2021**

## PRODUCT DESCRIPTION

DVX PPF Deep Prep Liquid prepares bodywork for paint protection film (PPF) and wrap installation. It removes wax, silicone, grease and fingerprint residue for optimal adhesive bonding. Its antistatic formula reduces dust and particle attraction to the surface during installation, for a clean finish without inclusions or bubbles.

## FEATURES

- Perfect surface for PPF
- Removes wax and silicone
- Antistatic
- Less dust under the film
- Better adhesion
- For professional installers

## DIRECTIONS FOR USE

1. **Wash** — Wash and decontaminate the vehicle, then dry.
2. **Apply** — Spray onto a panel or onto a clean microfiber.
3. **Wipe** — Wipe the whole surface until fully evaporated.
4. **Install** — Install the PPF film on the prepared surface.

## PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| **Product type** | Liquid car care product |
| **Appearance** | Liquid |
| **Odour** | Characteristic |
| **pH** | 6-7 |
| **Density (20 °C)** | 0,9-1 |
| **Use** | Concentrate — dilution 1:1–1:3 |

## PACKAGING

| Product Code | Pack Size | Units per Case | Barcode (EAN-13) |
|---|---|---|---|
| DVX2021 | 1 kg | 12 | — |

## STORAGE

Store in the original container, tightly closed, between 5 and 35 °C, in a cool, dry place away from direct sunlight. Protect from frost.

The expiry date, production date and lot number are printed on the pack.

## SAFETY INFORMATION

This mixture is not classified as hazardous under CLP. See the SDS for details.

The information in this sheet is based on our current knowledge and experience; users should test the product under their own conditions of use. For safety information, refer to the product Safety Data Sheet (SDS).

Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Istanbul Leather OIZ, Fikse St. No:20, 34935 Tuzla / Istanbul, Türkiye · +90 850 259 0389 · info@divortex.com.tr