

Safety Data Sheet (SDS)

Medium Power Stabilizer Anaerobic

AER1604

Product name on SDS	MEDIUM STRENGTH BOLT STABILIZER
Regulation	REACH Annex II — Regulation (EU) 2020/878 · CLP (EC) 1272/2008
Revision / date	Rev. 01 · 05.2022
Number of pages	14
Supplier	Setkim Kimya İnş. Taah. Paz. San. Tic. Ltd. Şti. · Divortex / DVX
Emergency	+90 216 669 03 53

This cover page identifies the product. The following pages are the official Safety Data Sheet prepared in accordance with applicable regulations and are presented unchanged.

SAFETY DATA SHEET

REPUBLIC OF TURKEY This document has been prepared in accordance with the Regulation on Safety Data Sheets for Hazardous Substances and Mixtures published in the Official Gazette dated 13/12/2014 and numbered 29204 by the Ministry of Environment and Urbanisation.

MEDIUM STRENGTH BOLT STABILIZER

Date of Issue: May 2022

Revision: 01 FORM: EF.55

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Identification of the Substance / Mixture: Medium Strength Bolt Stabilizer.

1.2 Use of the Substance / Mixture: Medium Strength Bolt Stabilizer (anaerobic threadlocker).

Uses advised against, if any: Do not use for cleaning hands, face, body or foodstuffs.

1.3 Company Identification

Manufacturer	SETKİM KİMYA İnş. Tah. Paz. San. Ve Tic. LTD. ŞTİ.
Address	İstanbul Leather Organized Industrial Zone, Plot V1, Fikse Cad. No:20 Tuzla/İSTANBUL
Tel.	0216 669 03 53
Fax.	0216 669 03 50
Contact	info@divortex.com.tr

1.4 Emergency Telephone No.: +90 216 669 03 53 · Türkiye: 114 UZEM

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

2.1 Classification of the Substance or Mixture

Physical Hazards

Not applicable

Health Hazards

Skin Sens. 1 H317

Eye Irrit. 2 H319

STOT SE 3 H335

Environmental Hazards

Not applicable

2.2 Label Elements

Hazard Pictogram;



Signal Word: Danger

Hazard Statements (H):

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

Precautionary Statements (P):

Prevention;

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly with water after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response;

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20
Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage;

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal;

P501 Dispose of contents/container in accordance with local regulations.

2.3 Other Hazards

PBT and vPvB assessment: Contains no PBT or vPvB substances.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Product name	EC no	CAS no	% concentration	Classification
Methacrylic acid, monoester with propane-1,2-diol	27813-02-1	248-666-3	60<80	Skin Sens. 1 H317 Eye Irrit. 2 H319
Cumene	202-704-5	98-82-8	0,1< 0,5%	Flam. Liq. 3 H226 Asp. Tox. 1 H304 STOT SE 3 H335 Aquatic Chronic 2 H411
Cumene hydroperoxide	201-254-7	80-15-9	1< 3%	Org. Perox. EF - H242 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 3 - H331 Skin Corr. 1B - H314 C≥10% Skin Irrit. 2 - H315 3%≤C<10% Eye Dam. 1 - H318 3%≤C<10% Eye Irrit. 2 - H319 1%≤C<3% STOT SE 3 - H335 C<10% STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

For the full text of each H statement see Section 16.

4. FIRST AID MEASURES

General Information: Seek medical assistance if any discomfort persists.

4.1 Inhalation: Remove the person from the danger area. Make sure the person gets fresh air. In case of unconsciousness, place in the stable recovery position and call a physician.

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20
Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

4.2 Skin contact: Remove all contaminated clothing. Wash thoroughly with plenty of water. May cause irritation; consult a physician.

4.3 Eye contact: Remove contact lenses. Immediately rinse with plenty of water while holding the eyelids open. Seek medical attention if discomfort persists.

4.4 Ingestion: Rinse your mouth thoroughly with water. Do not induce vomiting. Give plenty of water to drink. Consult a physician immediately. In case of vomiting, keep the head low. Call a POISON CENTER (Türkiye: 114) or a doctor.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: CO2, dry chemical powder (DCP), water spray, alcohol-resistant foam.

Unsuitable extinguishing media: A strong water jet and air mixture may cause explosions.

Chemicals with explosion risk: No risk of explosion.

Special advice for firefighters: No information available.

Special protective equipment: In case of fire, wear self-contained breathing apparatus independent of ambient air and chemicals. SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: Normal fire-fighting clothing, i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30), together with self-contained closed-circuit positive-pressure compressed-air breathing apparatus (BS EN 137).

Further information: Carbon dioxide, carbon monoxide and sulphur gas may be released on combustion.

Yangın Çeşitleri					**E**
Cinsi	Katı	Sıvı	Gaz	Metaller	Elektrik
Yanıcı Madde	Odun, Ahşap, Kumaş, Kağıt	Akaryakıt, yağ, boya, tiner	Metan, Propan, LPG	Magnezyum, Sodyum, alüminyum	Elektrik
Söndürme Yöntemi	Soğutma, yanmayı engelleme	Engelleme, boğma, soğutma	Engelleme	Soğutma, boğma	İlk iş elektriğin kesilmesi
Kullanılan Söndürücü	Su,ABC tozlu ve köpüklü söndürücü	ABC ve BC tozlu,halon gazlı, CO_2 ve köpüklü söndürücü	ABC ve BC tozlu,CO_2 vehalon gazlı söndürücü	Sadece D tozlu söndürücü	ABC ve B tozlu,halokarbon gazlı söndürücü

In general;

1. Dry powder fire extinguisher for "all kinds of fire".
2. Foam fire extinguisher for "solid and liquid fires".
3. Water fire extinguisher for "solid fires".
4. Halocarbon gas fire extinguisher may be used for "fires in electrical and electronic environments".

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. See Section 8. Avoid contact with eyes. Beware of slipping hazard.

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

6.2 Environmental precautions: Do not release into the environment. Prevent further leakage or spillage if safe to do so. Prevent entry into drains, basements and pits where accumulation may be hazardous. Inform the authorities if the product accidentally enters the sewer.

6.3 Methods and materials for containment and cleaning up: Remove all sources of ignition. Use explosion-proof equipment. Clean up all spills immediately. Absorb with liquid-binding material (e.g. universal binder, sand, diatomaceous earth). Keep waste in suitable closed containers. Collected material should be transferred to a suitable container and recovered, or disposed of in accordance with applicable national or regional regulations.

6.3.1 Advice on containing spillage:

Take protective measures against the risk of slipping.

6.3.2. Advice on cleaning up spillage: Take appropriate measures and clean up immediately after spillage. Collect liquid spills with dry sand, soil, silica gel or binder and place carefully in waste containers. Clean the remainder by diluting. Place contaminated material in a suitable container and dispose of it according to Section 13.

6.3.4 Other information:

Comply with local regulations. See Section 7 for safe handling, Section 8 for personal protective equipment and Section 13 for disposal. In case of an incident, apply the first aid measures in Section 4.

7. HANDLING AND STORAGE

7.1 Precautions for Safe Handling


Keep away from heat, sparks and flames. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, may burn and flash back even from a distance. Do not eat, drink or smoke during use. Remove all contaminated clothing and personal protective equipment before entering eating areas. Prevent release to the environment. Protect from sunlight. Do not expose to temperatures above 50 °C. Store in a well-ventilated place. Keep container tightly closed. Store locked up. To protect health, safety and the environment, work procedures and organisational measures must comply with Article 7 of the Regulation on Health and Safety Measures when Working with Chemical Substances (Official Gazette 12.8.2013, No. 28733) and Article 7 of the Regulation on Health and Safety Measures when Working with Carcinogenic or Mutagenic Substances (Official Gazette 6.8.2013, No. 28730), and care must be taken in planning work procedures and organisational measures at the workplace. Ensure handling in accordance with good industrial hygiene and safe handling procedures. Industrial hygiene standards must be observed to prevent ingestion and contact with eyes and skin. Common rules for working with chemicals must be followed. Ensure good ventilation at the workplace. Check concentrations in the workplace atmosphere against occupational exposure limits. This product is not self-igniting but must be kept under control in case of fire. See Section 7 for safe handling, Section 8 for personal protective equipment and Section 13 for disposal. Always follow the general hygiene rules for chemicals. Keep away from all sources of ignition. Avoid contact with skin and eyes. Never swallow the product. Do not eat, drink or smoke in the handling area. Avoid any ignition hazard. Avoid exposure to high temperatures during processing.

7.1.1 General Handling Advice:
7.1.1.1 Warnings for Safe Handling
Use protective clothing and avoid contact with clothing. Take the necessary measures to prevent or control fire in order to ensure safe handling of the substance or mixture. Use personal protective equipment. Ensure good ventilation. Avoid contact with eyes, skin and body. Keep away from sources of ignition. Keep fire-fighting equipment ready.
7.1.1.2 Warnings on incompatibilities of substances or mixtures
Take the necessary measures to prevent handling of incompatible substances or mixtures. Keep away from oxidising conditions, hot surfaces and flames.
7.1.1.3 Environmental Warnings
Prevent entry into sewers/surface water/groundwater. Inform the competent authorities if the product enters water or sewers.
7.1.1.4 Additional warnings:
Take the necessary measures to avoid damage to the original packaging/storage.
7.1.2. General Occupational Hygiene Advice:
Industrial hygiene standards must be observed to prevent ingestion and contact with eyes and skin during use. Wash hands with plenty of soap and water after work. Ensure good ventilation at the workplace. Smoking, eating and drinking must be prohibited in the application area. Remove contaminated clothing and protective equipment before entering eating areas.

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

7.2. Conditions for safe storage, including any incompatibilities
Handling precautions: Provide adequate local ventilation in storage areas. Keep away from food, drink and animal feedingstuffs. Store in a well-ventilated, dry and cool place away from heat, open flames and daylight. Keep containers closed. Do not eat, drink or smoke in the storage area. Keep away from all sources of ignition. Do not store together with oxidising agents, acids, alkalis or materials causing hazardous reactions. Recommended storage temperature: 0 °C to 35 °C. Do not exceed the expiry date shown on the packaging.

7.3. Specific end use(s)
Not available at present.



8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters
The mixture has no TWA or STEL values.

8.1.1.1 Occupational exposure limit values according to the Regulation on Health and Safety Measures when Working with Chemical Substances (O.G. 12.08.2013-28733): No data
8.1.1.2 Occupational exposure limit values according to the Regulation on Health and Safety Measures when Working with Carcinogenic or Mutagenic Substances (O.G. 06.08.2013-28730): No data

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

8.1.1.3 Other occupational exposure limit values: No data
8.1.1.4 Biological limit values according to the Regulation on Health and Safety Measures when Working with Chemical Substances (O.G. 12.08.2013-28733): No data
8.1.1.5 Other biological limit values: No data
8.1.2 Information on currently recommended monitoring procedures, at least for the most relevant substances: No data
8.1.3 Occupational exposure limits and/or biological limit values applicable to air contaminants formed when the substance or mixture is used as intended: No data
8.1.4 Where a control banding approach is used to decide on risk management measures for specific uses, sufficient information to enable effective management of the risk and the specific control band

Derived no-effect level DN(M)EL

Methacrylic acid, monoester with propane-1,2-diol;

Area of use	Route of exposure / environmental compartment	Health effect	Derived no-effect level	Value	Unit	Description
Worker/ employee	Human - inhalation	Long-term systemic effects	DNEL	14,7	mg/m^3	Repeated dose toxicity
Worker/ employee	Human - dermal	Long-term systemic effects	DNEL	4,2	mg/kg	Repeated dose toxicity
Consumer	Human - inhalation	Long-term systemic effects	DNEL	8,8	mg/m^3	Repeated dose toxicity
Consumer	Human - dermal	Long-term systemic effects	DNEL	5,7	mg/kg	Repeated dose toxicity
Consumer	Human - oral	Long-term systemic effects	DNEL	2,5	mg/kg	Repeated dose toxicity

Cumene;

Area of use	Route of exposure / environmental compartment	Health effect	Derived no-effect level	Value	Unit	Description
Worker/ employee	Human - inhalation	Long-term systemic effects	DNEL	16,6	mg/m^3	Irritation
Worker/ employee	Human - dermal	Long-term systemic effects	DNEL			
Consumer	Human - inhalation	Long-term systemic effects	DNEL			
Consumer	Human - dermal	Long-term systemic effects	DNEL			
Consumer	Human - oral	Long-term systemic effects	DNEL	5	mg/kg bw/day	Irritation

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

Protective Equipment:





Ventilation: Provide suitable extraction/ventilation at the workplace. Suitable respiratory protection should be used to keep the concentration below the workplace exposure limit.

Respiratory protection: No special equipment is required in well-ventilated areas. Use breathing apparatus in poorly ventilated areas.

Hand protection: Avoid direct contact. Protective gloves should be used for sensitive skin. (nitrile gloves EN 374)

Eye protection: Wear goggles with side shields or protective equipment. (EN 166)

Other protection: Follow the general hygiene rules for handling chemicals. Wash hands during breaks and after work. Keep away from food and drink. Remove contaminated clothing and protective equipment before entering eating areas.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Odour	Acrylate, characteristic
pH	Not applicable
Melting point / freezing point	Not applicable
Initial boiling point / boiling range	Not applicable
Flash point	>100 °C
Evaporation rate	Not applicable
Flammability	Not applicable
Upper / lower flammability or explosive limits	Not applicable
Vapour pressure	Not applicable
Vapour density	Not applicable
Relative density	1,03 gr/ml
Solubility	Insoluble in water
Log Pow (partition coefficient)	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Not applicable
Fluidity	Not applicable

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

Explosive / oxidising properties	Risk of explosion at temperatures above 50 °C
Viscosity	14000 – 16000 cPs

10. STABILITY AND REACTIVITY

Stability: Stable under normal temperature conditions.

Conditions to avoid: No information available.

Materials to avoid: Protect from sunlight. Do not expose to temperatures above 50 °C.

Hazardous reactivity: No information available.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

In the absence of experimental toxicological data on the product, its possible health hazards have been assessed on the basis of the properties of the substances it contains, according to the criteria of the applicable classification regulation. To assess the toxicological effects of exposure to the product, consider the concentrations of the individual substances listed in Section 3.

11.1.1 Acute Toxicity of the Substances;

Methacrylic acid, monoester with propane-1,2-diol;

Acute toxicity	Oral	LD50 >2000 mg/kg
	Inhalation	LD50 500-1000 mg/kg
	Dermal	LD50 (24 h) >5000 mg/kg

Cumene hydroperoxide;

Acute toxicity	Oral	LD50 1,2-1,52 mg/kg (rat)
	Inhalation	LC50 (4 h) 220 ppm
	Dermal	LD50 382 mg/kg

Cumene;

Acute toxicity	Oral	LD50 2910 mg/kg (rat)
	Inhalation	LC50 (1 h) 22,1 mg/L
	Dermal	LD50 (24 h) >3160 mg/kg

11.1.2 Skin Corrosion/Irritation

May cause irritation.

11.1.3 Serious Eye Damage/Irritation

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

No information.

11.1.4 Respiratory or Skin Sensitisation

May cause irritation.

11.1.5 Germ Cell Mutagenicity

No information is available on mutagenic ingredients.

11.1.6 Carcinogenicity

As stated in 29 CFR 1910.1200 (Hazard Communication), there is no information that this product contains carcinogenic substances as listed by NTP, IARC or OSHA.

11.1.7 Reproductive Toxicity

No information is available on ingredients toxic to reproduction.

11.1.8 Specific Target Organ Toxicity - Single Exposure (STOT SE)

STOT SE 3 H335

11.1.9 Specific Target Organ Toxicity - Repeated Exposure (STOT RE)

STOT SE 3 H335

11.2 Aspiration Hazard

No information.

11.3 Information on hazard classes, differentiation or effects

Skin Sens. 1 H317

Eye Irrit. 2 H319

STOT SE 3 H336

11.4 Hazard information on the mixture as placed on the market

Skin Sens. 1 H317

Eye Irrit. 2 H319

STOT SE 3 H336

11.5 Information on Test Data

No data

11.6 Additional supporting information on classification criteria

No data

11.7 Information on likely routes of exposure

Inhalation exposure: Prolonged inhalation may cause irritation of the respiratory tract.

Ingestion: May cause irritation of the mouth, throat and gastrointestinal tract, nausea and vomiting. Splashes on skin may cause redness and irritation. Splashes in the eyes may cause redness and watering of the eyes.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

The product is not expected to be hazardous to the environment.

12.1.1 Acute Toxicity:

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20
Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

Methacrylic acid, monoester with propane-1,2-diol;

Short-term toxicity to fish	LC50 (96 h) 833 mg/L
Short-term toxicity to aquatic invertebrates	EC50 (48 h) 210 mg/L NOEC (21 days) 45,2 mg/L
Toxicity to aquatic algae and cyanobacteria	EC50 (72 h) >97,2 mg/L

Cumene Hydroperoxide;

Short-term toxicity to fish	NOEC (96 h) 1,5 mg/L LC50 (96 h) 3,9 mg/L LC100 (48 h) 6 mg/L EC0 (24 h) 2,2 mg/L EC50 (24 h) 7 mg/L EC100 (24 h) 25 mg/L
Short-term toxicity to aquatic invertebrates	EC50 (48 h) 65-168,7 mg/L EC50 (24 h) 95-7802,83 mg/L
Toxicity to aquatic algae and cyanobacteria	EC50 (8 days) 7,4 mg/L EC50 (72 h) 3,1 mg/L NOEC (7 days) 1 mg/L

Cumene ;

Short-term toxicity to fish	LC50 (96 h) <2,9 mg/L LC50 (72 h) 4,8 mg/L LC50 (24 h) 8,1 mg/L EC50 (48 h) 2,14 mg/L NOEC (48 h) 1,6 mg/L
Short-term toxicity to aquatic invertebrates	EC50 (48 h) 5,7 mg/L EC50 (24 h) 2,45 mg/L NOEC (48 h) 1,6 mg/L
Long-term toxicity to aquatic invertebrates	NOEC (28 days) 0,38 mg/L NOEC (21 days) 0,35 mg/L
Toxicity to aquatic algae and cyanobacteria	EC50 (72 h) 2,01 mg/L NOEC (72 h) 1,35 mg/L EC10 (72 h) 0,697 mg/L

12.2 Persistence and Degradability:

Essentially biodegradable in water.

12.3 Bioaccumulative potential: Bioaccumulation is not expected.

12.4 Mobility in soil: Mobility in soil is not expected.

12.5 Results of PBT and vPvB assessment: Not applicable.

12.6 Other adverse effects:

Environmental hazards: Do not allow the product to enter sewage systems or watercourses.

Biological accumulation: The surfactants in this mixture comply with the biodegradability criteria laid down in Regulation (EC) No 648/2004.

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

13. DISPOSAL CONSIDERATIONS

Product: Dispose of in accordance with local regulations. According to the European Waste Catalogue, waste codes are not product-specific but application-specific. Waste codes should be assigned by the user, preferably in consultation with the waste disposal authorities.

Product residues: Recyclable container. Do not pierce or burn, even after use. Do not dispose of empty packaging with normal household waste. Containers should be recycled or reused. Packaging that is not empty should be treated as chemical waste.

Contaminated packaging: Dispose of as used product. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Local legislation: Disposal of waste must comply with applicable regional, national and local laws and regulations. Local regulations may be stricter than regional and national requirements and must be complied with.

14. TRANSPORT INFORMATION

The product is not classified as dangerous goods for transport.

ADR/RID; IMDG; ICAO/IATA: UN number: no data

ADR/RID; IMDG; ICAO/IATA: UN proper shipping name: no data

ADR/RID; IMDG; ICAO/IATA: Transport class: no data

ADR/RID; IMDG; ICAO/IATA: Packing group: no data

ADR/RID; IMDG; ICAO/IATA: Environmental hazards: no data

Special precautions for user: No information available

MARPOL: No information available.

15. REGULATORY INFORMATION

REPUBLIC OF TURKEY This document has been prepared in accordance with the Regulation on Safety Data Sheets for Hazardous Substances and Mixtures published in the Official Gazette dated 13/12/2014 and numbered 29204 by the Ministry of Environment and Urbanisation.

Regulation on the classification, labelling and packaging of substances and mixtures. Official Gazette 11/12/2013, No. 28848.

Regulation on the carriage of dangerous goods by road. Official Gazette 24/10/2013, No. 28801.

16. OTHER INFORMATION

Revision: Prepared for the first time. This SDS has been prepared in accordance with the Safety Data Sheet Regulation dated 13/12/2014, No. 29204. (English translation of the Turkish SDS.)

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

Abbreviations:

BHOT	Specific target organ toxicity
GBF	Safety Data Sheet
PBT	Persistent, bioaccumulative and toxic
DNEL	Derived no-effect level
vPvB	Very persistent and very bioaccumulative
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ADNR	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways on the Rhine
BCF	Bioconcentration factor
BetrSchV	Ordinance on Industrial Safety
CMR	Carcinogenic, mutagenic or toxic for reproduction
GLP	Good laboratory practice
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LOAEL	Lowest observed adverse effect level in animal studies
LOEL	Lowest observed effect level in animal studies
NOAEL	Highest dose causing no significant measurable harm even with continuous intake
OECD	Organisation for Economic Co-operation and Development
PNEC	Predicted no-effect concentration in an environmental medium
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
TA	Technical instruction
TRGS	Technical rules for hazardous substances
VCI	German Chemical Industry Association
VOC	Volatile organic compounds
VwVwS	Administrative regulation on the classification of substances hazardous to water
WGK	Water hazard class
EC50	Median effective concentration
BTOT	Specific target organ toxicity
OEL	Occupational exposure limits
PEC	Predicted environmental concentration

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20 Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50

NOEC	No observed effect concentration
NOEL	No observed effect level
ISO	International Organization for Standardization
DIN	German Institute for Standardization
TWA	Time-weighted average exposure concentration.
STEL	Limit value not to be exceeded over a 15-minute period.

This SDS has been prepared using information obtained from the supplier and from Annex 6 of the CLP (SEA) regulation.

Hazard statements:

H242 Heating may cause a fire.
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Prepared by: İrem Serra BEKTAŞ Document No: GBF-A-0-3048

Contact: Kadıköy / İSTANBUL Valid until: 12.11.2022

Setkim Kimya İnş. Tah. Paz. Sanayi Ticaret Ltd. Şti. İstanbul Deri Organize Sanayi Bölgesi V1 Nolu Parsel Fikse Cad. No:20
Tuzla, İstanbul /TÜRKİYE **T:** +90 (216) 669 03 52 **F:** +90 (216) 669 03 50